

# 20SK: Exercise #6

## Channel Coding (ECC)

Jan Přikryl

January 2, 2018

# Introduction

Source encoding: *Remove redundant information.*

Channel coding: *Protect data against transmission errors.*

Medium: *Controlled redundancy (increase message entropy).*

Always **block codes**

Linear codes

- ▶ Repetition code
- ▶ Hamming code
- ▶ BCH
- ▶ LDPC (Gallager, 1963)
- ▶ Cyclic codes (Reed-Solomon)

Other approaches:

- ▶ Convolution codes
- ▶ Turbo codes

# Problem 1

1. Assume a repetition code of block length  $n$  ( $n$  is odd) being used to transmit data over BSC with crossover probability  $\epsilon$  with simple majority vote decoding.
2. Determine the probability of uncorrected error in a block of length  $n$

# Problem 1

1. Assume a repetition code of block length  $n$  ( $n$  is odd) being used to transmit data over BSC with crossover probability  $\epsilon$  with simple majority vote decoding.
2. Determine the probability of uncorrected error in a block of length  $n$ 
  - 2.1 we will decode an incorrect bit if more than  $(n + 1)/2$  bits of the code word are corrupted

# Problem 1

1. Assume a repetition code of block length  $n$  ( $n$  is odd) being used to transmit data over BSC with crossover probability  $\epsilon$  with simple majority vote decoding.
2. Determine the probability of uncorrected error in a block of length  $n$ 
  - 2.1 we will decode an incorrect bit if more than  $(n + 1)/2$  bits of the code word are corrupted
  - 2.2 given  $\epsilon$ , probability that all  $k$  bits,  $k < n$ , will flip is  $\epsilon^k(1 - \epsilon)^{n-k}$

# Problem 1

1. Assume a repetition code of block length  $n$  ( $n$  is odd) being used to transmit data over BSC with crossover probability  $\epsilon$  with simple majority vote decoding.
2. Determine the probability of uncorrected error in a block of length  $n$ 
  - 2.1 we will decode an incorrect bit if more than  $(n + 1)/2$  bits of the code word are corrupted
  - 2.2 given  $\epsilon$ , probability that all  $k$  bits,  $k < n$ , will flip is  $\epsilon^k(1 - \epsilon)^{n-k}$
  - 2.3 given  $k$ , the total number of combinations containing  $k$  flipped bits a binomic number

# Problem 1

1. Assume a repetition code of block length  $n$  ( $n$  is odd) being used to transmit data over BSC with crossover probability  $\epsilon$  with simple majority vote decoding.
2. Determine the probability of uncorrected error in a block of length  $n$ 
  - 2.1 we will decode an incorrect bit if more than  $(n + 1)/2$  bits of the code word are corrupted
  - 2.2 given  $\epsilon$ , probability that all  $k$  bits,  $k < n$ , will flip is  $\epsilon^k(1 - \epsilon)^{n-k}$
  - 2.3 given  $k$ , the total number of combinations containing  $k$  flipped bits a binomic number
  - 2.4 we have to sum for every possible  $k$  from  $(n + 1)/2$  up to  $n$ , hence

$$p(n, \epsilon) = \sum_{k=(n+1)/2}^n \binom{n}{k} \epsilon^k (1 - \epsilon)^{n-k}.$$

## Problem 1 continued

3. Create function `rcbsc(n,ep)` computing probabilities of uncorrected errors for blocks of odd lengths up to  $n$  and plotting them using `stem()` into a graph.
4. Q: What would be the optimal length of the repetition code?
5. Q: What would be the code rate and transmission speed?
6. Q: How does it correspond to Shannon limit theorem? Discuss the difference.



## Problem 2

Assume linear code with a generator matrix  $\mathbf{G}$ .

1. Q: Given  $\mathbf{G}$ , what is the length of plain text vector  $\mathbf{v}$ ?
2. Q: How are codewords computed?
3. Q: How will you enumerate all codewords?
4. Write function `[C,dmin]=linprop(G)` that computes a binary matrix  $\mathbf{C}$  of all valid codewords for a linear code with generator matrix  $\mathbf{G}$  and determines the minimum code distance  $d_{\min}$ .

## Problem 2

Assume linear code with a generator matrix  $\mathbf{G}$ .

1. Q: Given  $\mathbf{G}$ , what is the length of plain text vector  $\mathbf{v}$ ?
2. Q: How are codewords computed?

$$\mathbf{w} = \mathbf{v}\mathbf{G}$$

3. Q: How will you enumerate all codewords?

4. Write function `[C,dmin]=linprop(G)` that computes a binary matrix  $\mathbf{C}$  of all valid codewords for a linear code with generator matrix  $\mathbf{G}$  and determines the minimum code distance  $d_{\min}$ .

## Problem 2

Assume linear code with a generator matrix  $\mathbf{G}$ .

1. Q: Given  $\mathbf{G}$ , what is the length of plain text vector  $\mathbf{v}$ ?
2. Q: How are codewords computed?

$$\mathbf{w} = \mathbf{v}\mathbf{G}$$

3. Q: How will you enumerate all codewords?

$$\mathbf{V} = \begin{bmatrix} 0 & 0 & \cdots & 0 \\ 0 & 0 & \cdots & 1 \\ \vdots & \vdots & \ddots & \vdots \\ 1 & 1 & \cdots & 1 \end{bmatrix}, \quad \mathbf{C} = \mathbf{V}\mathbf{G}$$

4. Write function `[C,dmin]=linprop(G)` that computes a binary matrix  $\mathbf{C}$  of all valid codewords for a linear code with generator matrix  $\mathbf{G}$  and determines the minimum code distance  $d_{\min}$ .

# Problem 3

## 1. Hamming encoding and decoding